

Make the body parts from a 2 X 4 planed to 11/4" thickness. Saw out and sand the three body parts to size and assemble as shown in the Figure. Now make the four wheels and leg parts from ½" stock and the ears from 1/8" stock. Assembly requires some careful work. To insure proper functioning, the parts should fit together so they move freely, but not sloppily. Sand all parts smooth and remove sharp corners and edges to make for smoother operation. I made the tail from a piece of leather attached securely with a small nail. Upholstery tacks make fine eyes. To get more traction on smooth surfaces, glue 80grit sandpaper "tires" around the wheels. Attach a screw eye to the nose for the pull string and doggie is ready to trail.

Devore O. Burch is a woodworker in Fort Worth, Texas, and a frequent contributor to Popular Woodworking.



Full-Size Patterns in the PullOut™ Plans Section

Coon Dog Cutting List						
		Rough Size				
Qty	Part	T	W	L	Piece	
1	Α	11/4"	3"	10"	head	
1	В	11/4"	2"	5"	center body	
1	С	11/4"	2"	6"	rear body	
4	D	1/2"	2" diameter		wheels	
4	Е	1/2"	1"	3"	legs	
4	F	1/2"	11/2"	21/2"	feet	
2	G	1/8"	11/2"	21/2"	ears	
Supplies						
4	#8 >	#8 X 3/4 flat head wood screws				
16	#8 >	#8 X 1" round head wood screws				
2	#8 >	#8 X 1/2" round head wood screws				

work properly.